## **Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application. Please cancel claims 1-6, amend claim 7, and add claims 8-26 as follows:

- 1. (Cancelled)
- 2. (Cancelled)
- 3. (Cancelled)
- 4. (Cancelled)
- 5. (Cancelled)
- 6. (Cancelled)
- 7. (Amended) A method for efficient encryption and decryption of Internet, Intranet, or e-mail messages, comprising the steps of:

providing a sending unit in communication with an integrated encryption circuit embedded with an encryption algorithm;

encrypting a message at a <u>said</u> sending unit <u>which</u> is to be sent to a receiving unit using an integrated circuit embedded with an algorithm located within said sending unit;

appending to the message at said sending unit the <u>a</u>receiver's unencrypted IP address;

appending to said message the-a\_receiver's encrypted IP address;

said sending unit sends sending said encrypted message with said unencrypted IP address and said encrypted IP address to a receiving unit;

providing said receiving unit having an integrated encryption circuit embedded with a decryption algorithm;

receiving unit with an integrated circuit embedded with an encryption algorithm located within saidreceiving with said receiving unit said encrypted message with said unencrypted IP address and said encrypted IP address;

receiving unit decryptsdecrypting with said receiving unit said encrypted IP address, thereby resulting in a decrypted IP address; storing said decrypted IP address in a register built into said integrated circuit embedded encryption algorithm within said receiving unit

storing said decrypted IP address in a first register built into said integrated encryption circuit within said receiving unit;

receiving unit storesstoring said unecrypted IP address into a <u>second</u> register built into said integrated circuit embedded with an encryption algorithm located within <u>said</u> receiving unit;

means for comparing said <u>second</u> register storing unencrypted IP address to said first register storing <u>said</u> decrypted IP address;

receiving unit decryptsdecrypting said message if said second register storing said unencrypted IP address matches said first register storing said decrypted encrypted IP address; and

means for halting decryption process if said <u>second</u> register storing <u>said</u> unencrypted IP address does not match said <u>first</u> register storing <u>encryptedsaid</u> <u>decrypted</u> IP address.

8. (New) A method of encrypting Internet, Intranet, or e-mail messages, comprising:

providing a communication device in communication with a private encryption
key generator;
generating a primary private encryption key;
encrypting data with the primary private encryption key;
providing a public encryption key and a second private encryption key pair;
encrypting the primary private encryption key with the public encryption key and
second private encryption key pair; and
sending the data encrypted with the primary private encryption key and the primary private encryption key encrypted with the public encryption key and second private encryption key pair to a receiving unit.
9. (New) The method of claim 8, wherein access to the private encryption key generator is password controlled.
10. (New) The method of claim 9 wherein the password is user defined.
11. (New) The method of claim 8 wherein said encryption key generator is located within a communication device.
12. (New) The method of claim 8 wherein the primary private key is randomly generated.
13. (New) A method of decrypting Internet, Intranet, e-mail messages, comprising:
providing a communication device in communication with a private encryption key generator;
receiving an encrypted message with the communication device, the message
having data encrypted with a primary private encryption key and a primary private

Appl. No.: 09/490,941

Resp to Notice of Non-Compliant Amendment

encryption key encrypted with a public encryption key and second private encryption
key pair;
providing access to the private encryption key generator;
decrypting the public encryption key and second private encryption key pair with
the primary encryption key generator, thereby providing the primary private encryption
key; and
decrypting the data with the primary private encryption key.
14. (New) The method of claim 13 wherein access to the private encryption key
generator is password controlled.
15. (New) The method of claim 14 wherein the password is user defined.
16. (New) The method of claim 13 wherein access to the primary encryption key
generator requires verification.
17. (New) The method of claim 16 wherein the verification comprises a Certificate of
Authority.
18. (New) A method of encrypting Internet, Intranet, or e-mail messages, comprising
the steps of:
providing a communication device in communication with an integrated
encryption circuit embedded with encryption algorithms;
accessing the integrated encryption circuit to encrypt a message;
encrypting the message with the encryption algorithms;
providing a message header comprising the sender's private cipher key and a
digital bit array;

Appl. No.: 09/490,941

Resp to Notice of Non-Compliant Amendment

encrypting the message header using a receiver's public encryption key;
appending the encrypted message header to the encrypted message; and
transmitting the encrypted message header and the encrypted message to a
receiver.
19. (New) The method of claim 18 wherein the message is transmitted through an
Internet.
20. (New) The method of claim 18 wherein the message is transmitted through an
Intranet.
21. (New) The method of claim 18 wherein the message is transmitted through an e-
<u>mail.</u>
22. (New) The method of claim 18 wherein the message is transmitted through a
wireless communication system.
23. (New) A method of decrypting a message of claim 18 further comprising the
steps of:
providing a communication device in communication with an integrated
decryption circuit;
receiving an encrypted message and encrypted message header with the communication device;
<u>communication device,</u>
accessing the integrated decryption circuit to decrypt the encrypted message and message header;
message neader,
decrypting the message header with the decryption circuit;
validating the message header with the decryption circuit;

